

# S-SERIES

compatible to: DENTSPLY Implants® / Astra Tech Implant System OsseoSpeed® TX



## PLATFORM

3,5 / 4,0 mm

4,5 / 5,0 mm

## TITANIUM BASE

for individual milled  
Zirconium Abutment  
incl. screw  
Titanium Grade 5 ELI



S 800

S 820



## SCAN BODY 3D-GUIDE®

for intra + extra  
oral scanning



S 9.S3D3.540

S 9.S3D4.550



## LAB ANALOG

Stainless Steel



S 50

S 52



## IMPLANT PICK-UP

for open-tray with  
integrated screw



S TR-00013.5

S TR-00024.5

## ABUTMENT SCREW

Recommended tightening  
torques 25 Ncm  
Titanium Grade 5 ELI



S 60

S 61



Notice: Products indicated with ® and ™ are registered brand names of the respective manufactures.  
Products indicated with ★ are available in the USA 

**NEXT GENERATION DESIGN – MADE IN GERMANY** 

# S-SERIES

compatible to: DENTSPLY Implants® / Astra Tech Implant System OsseoSpeed® TX



## PLATFORM

3,5 / 4,0 mm

3,5 / 4,0 mm

4,5 / 5,0 mm

## STRAIGHT ABUTMENT

Gingiva Height 1,5 mm  
incl. screw  
Titanium Grade 5 ELI



S 100

S 110

S 120



## STRAIGHT ABUTMENT

Gingiva Height 3,0 mm  
incl. screw  
Titanium Grade 5 ELI



S 100-3

S 110-3

S 120-3



## ANGLED ABUTMENT 16°

angled over surface  
Gingiva Height 1,5 mm  
incl. screw  
Titanium Grade 5 ELI



S 200

S 210

S 220

## ANGLED ABUTMENT 16°

angled over surface  
Gingiva Height 3,0 mm  
incl. screw  
Titanium Grade 5 ELI



S 200-3

S 210-3

S 220-3

## ABUTMENT SCREW

Recommended tightening  
torques 25 Ncm  
Titanium Grade 5 ELI



S 60

S 60

S 61



# S-SERIES

compatible to: DENTSPLY Implants® / Astra Tech Implant System OsseoSpeed® TX



## PLATFORM

3,5 / 4,0 mm

4,5 / 5,0 mm

## STRAIGHT MASSIV ABUTMENT

incl. 2 screws

Titanium Grade 5 ELI



S 400

S 420



## UCLA ABUTMENT

engaging

incl. screw



S 11.CA3.540

S 11.CA4.550

## ABUTMENT SCREW

Recommended tightening

torques 25 Ncm

Titanium Grade 5 ELI



S 60

S 61



Notice: Products indicated with ® and ™ are registered brand names of the respective manufactures.  
Products indicated with ★ are available in the USA 

**NEXT GENERATION DESIGN – MADE IN GERMANY** 

# S-SERIES

compatible to: DENTSPLY Implants® / Astra Tech Implant System OsseoSpeed® TX



## PLATFORM

3,5 / 4,0 mm

4,5 / 5,0 mm

## 2-CONNECT®-ABUTMENT SET

incl. 2-CONnect®-Coping  
and Coping-screw  
Titanium Grade 5 ELI



Gingiva Height

0,5 mm	S 800 S	S 820 S	★
2,5 mm	S-2CON 8035402S	S-2CON 8045502S	★

## 2-CONNECT®-ABUTMENT

Recommended tightening  
torques 25 Ncm  
Titanium Grade 5 ELI  
M (Male Part)



Gingiva Height

0,5 mm	S 800 M	S 820 M	★
2,5 mm	S-2CON 8035402M	S-2CON 8045502M	★

## 2-CONNECT®-COPING

Titanium Grade 5 ELI



F (Female Part)

2CON F-U	2CON F-U	★
----------	----------	---

## COPING-SCREW

Recommended tightening  
torques 20 Ncm  
Titanium Grade 5 ELI



KS 61

KS 61	KS 61	★
-------	-------	---

# S-SERIES

compatible to: DENTSPLY Implants® / Astra Tech Implant System OsseoSpeed® TX

NEW



## PLATFORM

3,5 / 4,0 mm

4,5 / 5,0 mm

## 2-CONNECT®-ABUTMENT SET

incl. 2-CONnect®-Coping,  
Coping-screw & Male Part Screw  
angled 20°

Gingiva Height 2,5 mm

Titanium Grade 5 ELI

Coming soon



S-2CON 80354A3S

S-2CON 80455A3S

## 2-CONNECT®-ABUTMENT

angled 20°

Gingiva Height 2,5 mm

Titanium Grade 5 ELI

Coming soon

M (Male Part)



S-2CON 80354A3M

S-2CON 80455A3M

## 2-CONNECT®-COPING

Titanium Grade 5 ELI



F (Female Part)

2CON F-U

2CON F-U

★

## COPING-SCREW

Recommended tightening  
torques: 15 Ncm

Titanium Grade 5 ELI

Coming soon



KS 62

KS 62

## MALE PART SCREW

for angled 20° 2-CONnect®  
Abutment | Recommended  
tightening torques: 20 Ncm

Titanium Grade 5 ELI

Coming soon



S 6.Ms3.540

S 6.Ms4.550

Notice: Products indicated with ® and ™ are registered brand names of the respective manufactures.  
Products indicated with ★ are available in the USA 

NEXT GENERATION DESIGN – MADE IN GERMANY ///

# S-SERIES

compatible to: DENTSPLY Implants® / Astra Tech Implant System OsseoSpeed® TX



## PLATFORM

3,5 / 4,0 mm

4,5 / 5,0 mm

## 2-CONNECT®- IMPLANT PICK-UP integrated screw



● Straight KS 61 =  $\varnothing$  1,8 mm

2CON TR-00021.8

2CON TR-00021.8

● Angled KS 62 =  $\varnothing$  1,6 mm

2CON TR-00031.6

2CON TR-00031.6

## 2-CONNECT®- SCAN BODY 3D-GUIDE® for intra + extra oral scanning



● Straight KS 61 =  $\varnothing$  1,8 mm

2CON 9.S3D1.800

2CON 9.S3D1.800

★

● Angled KS 62 =  $\varnothing$  1,6 mm

2CON 9.S3D1.600

2CON 9.S3D1.600

★

## 2-CONNECT®- LAB ANALOG Stainless Steel



● Straight KS 61 =  $\varnothing$  1,8 mm

2CON 5.La1.800

2CON 5.La1.800

★

● Angled KS 62 =  $\varnothing$  1,6 mm

2CON 5.La1.600

2CON 5.La1.600

★

## 2-CONNECT®- DIM ANALOG



● Straight KS 61 =  $\varnothing$  1,8 mm

2CON 5.DIM.180

2CON 5.DIM.180

★

● Angled KS 62 =  $\varnothing$  1,6 mm

2CON 5.DIM.160

2CON 5.DIM.160

★

## SLEEVE plaster model Stainless Steel



DIM 5.XSL.A30

DIM 5.XSL.A30

★

Notice: Products indicated with ® and ™ are registered brand names of the respective manufactures.  
Products indicated with ★ are available in the USA 

# S-SERIES

compatible to: DENTSPLY Implants® / Astra Tech Implant System OsseoSpeed® TX



## PLATFORM

3,5 / 4,0 mm

4,5 / 5,0 mm

## NT-PREFORM®

incl. coloured milling screw  
Titanium Grade 5 ELI



Gingiva Height

1,3 mm

0,5 mm

S 10.Mi3.540

S 10.Mi4.550

★

S 10.Mi3.540.05

S 10.Mi4.550.05

★

## NT-MILL LAB ANALOG

for nt-Preform®  
Stainless Steel



groove



groove

S 5.La3.540

S 5.La4.550

★

## ABUTMENT GRIP

for nt-Holder fixture  
Stainless Steel



W 12.100.000

W 12.200.000

★

## SCAN BODY 3D-GUIDE®

for intra + extra  
oral scanning



S 9.S3D3.540

S 9.S3D4.550

★

## COLOURED MILLING SCREW

for nt-Preform®  
Recommended tightening  
torques 10 Ncm



S 6.Sc3.540

S 6.Sc4.550

★

## ABUTMENT SCREW

Recommended  
tightening torques 25 Ncm  
Titanium Grade 5 ELI



S 60

S 61

★

Notice: Products indicated with ® and ™ are registered brand names of the respective manufactures.  
Products indicated with ★ are available in the USA

**NEXT GENERATION DESIGN – MADE IN GERMANY ///**

# S-SERIES DIM ANALOG

compatible to: DENTSPLY Implants® / Astra Tech Implant System OsseoSpeed® TX



## PLATFORM

3,5 / 4,0 mm

4,5 / 5,0 mm

## DIM ANALOG



S 5.DIM.354

S 5.DIM.455



## SLEEVE

for plaster model  
Stainless Steel



DIM 5.XSL.A10

DIM 5.XSL.A20



Notice: Products indicated with ® and ™ are registered brand names of the respective manufactures.  
Products indicated with ★ are available in the USA 

**NEXT GENERATION DESIGN – MADE IN GERMANY** ///